

BVA3 & BVA5 Ex Series

ATEX Air Intake Shutdown Butterfly Valve

(Energized to open / Fail safe)

gali

BVA-CA_en-a



BVA3 Ex Series



BVA5 Ex Series

- Suitable for both **naturally aspirated and turbo charged engines**.
- Available with a **microswitch to indicate valve status** (open or closed).
- **Mountable in any position**.
- Operating **temperature range**: -25°C to +60°C.

- **ATEX Zone 1**  certified version is available ensuring compliance and safety in the most demanding environments.
- Our valve is **designed to replace existing installations without modifications**. Fully compatible with most market valves, it ensures a cost-effective upgrade.

Diesel engines are at risk of uncontrolled overspeed. The **GALI Butterfly Valve Ex** is specifically designed to be **installed in the air intake line of a diesel engine**, providing **fast emergency shutdown to prevent engine runaway**.

The valve is **energized to open and fails safe**. In the event of a **power failure or emergency**, the

valve closes automatically, stopping the engine within seconds to prevent damage or disaster.

Constructed from corrosion-resistant materials, the GALI valve is built for durability and performance. It is **adaptable to a wide range of pipe sizes through the use of hose adaptors**, ensuring a perfect fit for your engine configuration.


GALI INTERNACIONAL, SA | C/ Josep Tura, 5, 08181 | Sentmenat (BCN) SPAIN | T +34 93 715 31 11
gali@galigrup.com | www.galigrup.com | www.galigrup.cn

SPAIN spain@galigrup.com **GERMANY** germany@galigrup.com **FRANCE** france@galigrup.com **ITALY** italy@galigrup.com
CHINA china@galigrup.com **SINGAPORE** singapore@galigrup.com **JAPAN** japan@galigrup.com

BVA3 & BVA5 Ex Series

Air Intake Shutdown Butterfly Valve

(Energized to open / Fail safe)



TECHNICAL DATA

Valve size	BVA3 Ex (3")	BVA5 Ex (5")
Current / Voltage	60A (pull) + 1A (hold) @ 12VDC	
	30A (pull) + 0,5A (hold) @ 24VDC	
	Cable length 5 m	
Temperature	Ambient: min. -25°C / max. +60°C	
	Air intake: max. +120°C	
Micro switch	DC Switching Capacity @30V: 7A Ohmic Load / 5A Inductive Load	
	Cable length 5 m	
Maximum allowable tension time for actuation of the traction solenoid	1,5 seconds	
Maximum number of drive cycles	6 cycles every 30 minutes (30 minutes to cool down between each period)	
Recommended setting for the drive of the traction solenoid in the stop controller	1 second	

Adapters for 3" / Ø76 mm valve

Reference	ØAmm / ØA[in]	B(mm) / B[in]
BV31038	38 / [1 1/2]	51 / [2]
BV31044	44.5 / [1 3/4]	50 / [2]
BV31051	51 / [2]	49 / [1,9]
BV31057	57 / [2 1/4]	47 / [1,8]
BV31060	60 / [2 3/8]	47 / [1,8]
BV31063	63.5 / [2 1/2]	46 / [1,8]
BV31067	67 / [2 5/8]	46 / [1,8]
BV31070	70 / [2 3/4]	45 / [1,8]
BV31076	76 / [3]	44 / [1,7]
BV31082	82.5 / [3 1/4]	43 / [1,7]
BV31089	89 / [3 1/2]	30 / [1,2]
BV31102	102 / [4]	42 / [1,7]

Adapters for 5" / Ø127 mm valve

Reference	ØA(mm) / ØA[in]	B(mm) / B[in]
BV51089	89 / [3 1/2]	59 / [2,3]
BV51095	95 / [3 3/4]	58 / [2,3]
BV51102	102 / [4]	57 / [2,2]
BV51108	108 / [4 1/4]	54 / [2,1]
BV51114	114 / [4 1/2]	52 / [2]
BV51121	121 / [4 3/4]	50 / [2]
BV51127	127 / [5]	48 / [1,9]
BV51140	140 / [5 1/2]	42 / [1,7]
BV51152	152 / [6]	39 / [1,6]

GALI INTERNACIONAL, SA | C/ Josep Tura, 5, 08181 | Sentmenat (BCN) SPAIN | T +34 93 715 31 11
gali@galigrup.com | www.galigrup.com | www.galigrup.cn

SPAIN spain@galigrup.com GERMANY germany@galigrup.com FRANCE france@galigrup.com ITALY italy@galigrup.com
CHINA china@galigrup.com SINGAPORE singapore@galigrup.com JAPAN japan@galigrup.com